

Sezione Size conductor [mm ²]	Formazione conduttore Conductor stranding [N° x mm]	Resistenza elettrica Electrical resistance [Ω/Km]	Diametro su isolamento Diameter on insulation [mm]	Spessore di isolamento Radial thickness of insulation [mm]
0.75	24 x 0.193	≤ 26.0	2.33 ± 0.1	≥ 0.60
1	32 x 0.193	≤ 19.5	2.47 ± 0.1 (H05BQ-F) 2.85 ± 0.1 (H07BQ-F)	≥ 0.60 (H05BQ-F) ≥ 0.80 (H07BQ-F)
1.5	28 x 0.243	≤ 13.3	3.05 ± 0.1	≥ 0.80
2.5	48 x 0.243	≤ 7.98	3.8 ± 0.1	≥ 0.90
4	52 x 0.300	≤ 4.95	4.5 ± 0.1	≥ 1.0
6	80 x 0.300	≤ 3.30	5.25 ± 0.1	≥ 1.0
10	136 x 0.300	≤ 1.91	6.6 ± 0.1	≥ 1.2
16	210 x 0.300	≤ 1.21	7.6 ± 0.1	≥ 1.2

Sezione Size conductor [mm ²]	Diametro esterno Outer diameter [mm]	Spessore guaina Thickness of jacket [mm]
H05BQ-F	2 x 0.75	6.2 ± 0.2
	3 x 0.75	6.7 ± 0.2
	4 x 0.75	7.3 ± 0.2
	5 x 0.75	8.3 ± 0.2
	2 x 1	6.7 ± 0.2
	3 x 1	7.1 ± 0.2
	4 x 1	7.8 ± 0.2
	5 x 1	8.55 ± 0.2
H07BQ-F	2 x 1	7.6 ± 0.2
	3 x 1	8.1 ± 0.2
	4 x 1	9.0 ± 0.2
	5 x 1	10.1 ± 0.3
	2 x 1.5	8.1 ± 0.2
	3 x 1.5	8.6 ± 0.2
	4 x 1.5	9.6 ± 0.2
	5 x 1.5	10.5 ± 0.3
	2 x 2.5	9.8 ± 0.2
	3 x 2.5	10.4 ± 0.3
	4 x 2.5	11.6 ± 0.3
	5 x 2.5	12.9 ± 0.3

Sezione Size conductor [mm ²]	Diametro esterno Outer diameter [mm]	Spessore guaina Thickness of jacket [mm]
H07BQ-F	2 x 4	11.4 ± 0.3
	3 x 4	12.2 ± 0.3
	4 x 4	13.5 ± 0.3
	5 x 4	15.0 ± 0.3
	2 x 6	13.1 ± 0.3
H07BQ-F	3 x 6	14.2 ± 0.3
	4 x 6	15.7 ± 0.3
	5 x 6	17.4 ± 0.3
	2 x 10	17.4 ± 0.3
	3 x 10	18.7 ± 0.3
H07BQ-F	4 x 10	20.5 ± 0.3
	5 x 10	22.6 ± 0.3
	2 x 16	19.6 ± 0.3
	3 x 16	21.3 ± 0.3
	4 x 16	23.0 ± 0.3
H07BQ-F	5 x 16	25.8 ± 0.3