



**SALCAVI
INDUSTRIE**

TECHNICAL DATA SHEET



© All rights reserved.

All contents of this document are our property and any copy or divulgation is not allowed without our written authorization.

Sezione <i>Size conductor</i> [mm ²]	Formazione conduttore <i>Conductor stranding</i> [N° x mm]	Resistenza elettrica <i>Electrical resistance</i> [Ω/Km]	Diametro su isolamento <i>Diameter on insulation</i> [mm]	Spessore di isolamento <i>Radial thickness of insulation</i> [mm]
1	32 x 0.193	≤ 19.5	2.85 ± 0.1	≥ 0.80
1.5	28 x 0.243	≤ 13.3	3.05 ± 0.1	≥ 0.80
2.5	48 x 0.243	≤ 7.98	3.8 ± 0.1	≥ 0.90
4	52 x 0.300	≤ 4.95	4.5 ± 0.1	≥ 1.0
6	80 x 0.300	≤ 3.30	5.25 ± 0.1	≥ 1.0

Sezione <i>Size conductor</i> [mm ²]	Diametro esterno <i>Outer diameter</i> [mm]	Spessore guaina <i>Thickness of jacket</i> [mm]
2 x 1	8.0 ± 0.2	≥ 1.3
3 x 1	8.8 ± 0.2	≥ 1.4
4 x 1	9.7 ± 0.2	≥ 1.5
5 x 1	10.6 ± 0.3	≥ 1.6
2 x 1.5	9.0 ± 0.2	≥ 1.5
3 x 1.5	9.6 ± 0.2	≥ 1.6
4 x 1.5	10.5 ± 0.3	≥ 1.7
5 x 1.5	11.5 ± 0.3	≥ 1.8
2 x 2.5	10.7 ± 0.3	≥ 1.7
3 x 2.5	11.6 ± 0.3	≥ 1.8
4 x 2.5	12.6 ± 0.4	≥ 1.9
5 x 2.5	13.9 ± 0.4	≥ 2.0

Sezione <i>Size conductor</i> [mm ²]	Diametro esterno <i>Outer diameter</i> [mm]	Spessore guaina <i>Thickness of jacket</i> [mm]
2 x 4	12.3 ± 0.4	≥ 1.8
3 x 4	13.2 ± 0.4	≥ 1.9
4 x 4	14.4 ± 0.4	≥ 2.0
5 x 4	16.1 ± 0.4	≥ 2.2
2 x 6	14.1 ± 0.4	≥ 2.0
3 x 6	14.8 ± 0.4	≥ 2.1
4 x 6	16.5 ± 0.4	≥ 2.3
5 x 6	18.5 ± 0.4	≥ 2.5

Revision Date
07/09/2017

Issue n.
2.0

Approved by
UTC

Page: 2 / 3

Al fine di perfezionare i nostri prodotti, le informazioni contenute in questa scheda possono essere variate senza preavviso. Preghiamo verificare con i ns. uffici la data e il numero di revisione.
In order to improve our products, the information contained in this technical data sheet can be changed without notice. Please check periodically with our offices date and number of the revision.



+39 0541 921101 +39 0541 921494 info@salcavi.com

www.salcavi.com

